


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Stephen Hardley

Dated 22 December 2004

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

1977

**The
Patent
Office**

05DED05 E85725815 D01058
P01/7700 0.00-032816047**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

 Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

P513590GB/DCJ/51103

2. Patent application number

04 DEC 2003

0328160.7

(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)
 Imperial Chemical Industries plc.
20 Manchester Square
London
W1U 3AN
United Kingdom
Patents ADP number (*if you know it*)

00000935006

If the applicant is a corporate body, give the country/state of its incorporation

UK ALL 5/104

4. Title of the invention

Container Closure Arrangement

5. Name of your agent (*if you have one*)
 "Address for service" in the United Kingdom
to which all correspondence should be sent
(*including the postcode*)

 WITHERS & ROGERS
Goldings House
2 Hays Lane
London
SE1 2HW
Patents ADP number (*if you know it*)

1776001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number
(*if you know it*)Date of filing
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(*day / month / year*)8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

YES

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	5
Claim(s)	2
Abstract	0
Drawing (s)	3 + 3

10. If you are also filing any of the following, state how many against each item.

Priority documents	0
Translations of priority documents	0
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	0
Request for preliminary examination and search (Patents Form 9/77)	1
Request for substantive examination (Patents Form 10/77)	0
Any other documents (please specify)	

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

Withers & Rogers

WITHERS & ROGERS

4th December 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

D Colin Jones

+44 (0)20 7663 3500

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

P513590GB

Container Closure Arrangement

This invention relates to a closure arrangement for a container and to a container closed thereby. The closure arrangement is conveniently relockable. The invention finds 5 particular, though not exclusive, application to closing containers of liquids, for example paint.

Cans of paint, for example, are often simply closed with a lid that has an outwardly-directed rim that is press-fitted into the top of the container. Removal of the 10 lid may be made by means of insertion of the blade of a screwdriver and twisting to prise off the lid. The lid can subsequently be replaced to re-close the container, but usually the mating surfaces of the lid and container become damaged, and can become coated with dried contents of the container, with the result that a significant effort has to be exerted to re-close the container, and even then a seal may not be effected, which can 15 cause spillage and/or deterioration of the contents.

More complex closure arrangements are also known. WO 03/062081 A1 discloses a relockable closure for a container, comprising a cover and a skirt that is foldable to lock the cover onto the container. The closure requires a convoluted curl shape to be formed 20 on the outside of the container at its rim. A metal cover for the container is provided with a separate peripheral skirt attached thereto that depends downwardly therefrom and has a fold point that allows a curved rib to be deployed downwards so as to engage beneath the curl of the container. A sealing compound is provided between the metal cover and the rim of the container. The skirt may be separated into a plurality of 25 sections by slits to facilitate its folding down around the outside of the container so as releasably to lock the cover thereon. It will be appreciated that this closure requires several components and complex shaping in order to be effective.

US-A-3688942 discloses a simpler form of container and closure combination, in 30 which the body of the container at its open end is shaped to provide a radially-outwardly and downwardly directed peripheral skirt portion. The closure is

also provided with a peripheral skirt portion with a plurality of latch members attached thereto by integral flexible hinge walls. The latch members engage the free edge of the container skirt portion in a cam and cam follower manner so as to secure the closure to the container, with a compressible seal being provided therebetween.

5

Whilst each of WO 03/062081 A1 and US-A-3688942 provides a relockable closure for a container, release of the cover from the container is effected by a part thereof that extends beyond the periphery of the container, which can give rise to unintentional freeing of the closure and risk of spillage of the contents of the container.

10

In accordance with one aspect of the present invention, there is provided closure arrangement for a container, wherein the container has a peripheral wall defining a rim enclosing an opening at one end thereof, the peripheral wall having at least one outwardly-directed projection extending at least partially around the outer surface of the 15 wall adjacent the opening, and wherein a cover is provided for releasably closing the opening, the cover having a surface for closing the opening of the container and a skirt depending therefrom to enclose the projection of the container, the skirt being provided with (a) at least one hinged locking member that has an inwardly-directed projection for co-operating with the outwardly-directed projection of the container, and (b) a lip for 20 engaging over the rim of the container at the opening thereof, thereby to lock the cover to the container, with the respective inwardly-and outwardly-directed projections engaging with each other.

25 The closure arrangement of the present invention requires comparatively few components, comprising in its most basic form, a suitably-shaped rim of a container, and a cover that serves to close the container and to effect locking thereonto by one, or more, integral hinged locking members.

30 With locking of the container being brought about by an upward movement of the locking member(s) to effect, preferably a snap-fit, connection over the rim of the container, the free ends of the locking members may be contained within the periphery of the container, thus mitigating against accidental release.

It will be appreciated that the snap-fitting of the locking members will provide an indication to the user that they are securely in place.

- 5 The cover and the skirt are preferably formed integrally with one another, and the or each locking member is preferably formed integrally with the skirt, preferably being hinged thereto by a living hinge. Alternatively, the or each locking member may be secured to the skirt by a respective separate hinge.
- 10 Preferably, a window is formed in the skirt at the peripheral location of the or each locking member, whereby upon locking the cover onto the container, the locking member fits into its window and the respective inwardly- and outwardly-directed projections engage each other directly.
- 15 Since the cover and the container, in the absence of any liner, will be in contact with the contents of the container, they will be made from a relatively inert material. For example, they may be made of a plastics material, preferably by moulding. However, it is also envisaged that metal may be used in appropriate circumstances.
- 20 Preferably three locking members are provided for a closure arrangement of generally circular configuration, being equi-spaced around the cover, although two, or four or more, may be used if required. Where the configuration is rectilinear, then it is envisaged that at least one locking member would be provided for each side of the arrangement.
- 25 Whilst preferably the outwardly-directed projection on the surface of the container extends continuously therearound, it is envisaged that it may be provided by a plurality of discrete sections. In the latter case, the number of sections would advantageously be the same as the number of locking members, thus requiring the cover to be appropriately positioned on the container in order to effect locking therebetween.
- 30

In accordance with another aspect of the present invention, there is provided the combination of a container and a closure arrangement in accordance with the said one aspect of the present invention.

5 A closure arrangement for a container will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a plan view of the arrangement with two locking members thereof in the locked state and a third locking member in the unlocked state;

10 Figure 2 is a sectional elevation on the line A-A of Figure 1 showing the closure arrangement in the unlocked state; and

Figure 3 is a sectional elevation on the line B-B of Figure 1, showing the closure arrangement in the locked state.

15 Referring to the Figures, a cylindrical container 2, made of a plastics material for containing emulsion paint, is closed by a moulded plastics cover 4. The container 2 has a generally rectangular-sectioned projection 6 extending circumferentially therearound on its outer surface, adjacent a rim 8 at its open end.

20 The cover 4 has a planar dished upper surface 10 that sits within the container rim 8, and has three hinged locking members 12 equi-spaced therearound which are set into a downwardly-depending skirt 14 of the cover 4. The cylindrical inner surface of the skirt 14 is of such a diameter as to form a sliding fit over the circumferential projection 6 on the outside of the container 2.

25

Each locking member 12 is formed interally with the skirt 14 and can be hinged away from the lower circumferential edge 16 thereof by means of a live hinge 18 (Figure 2) exposing a window 15 in the skirt 14. The hinged portion of the locking member 12 is of generally L-shape, having a lower part 13 extending away from the hinge 18 that is

30 provided adjacent thereto with an inwardly-directed generally rectangular-sectioned projection 20, of generally the same size and shape as the container projection 6. The projections 6 and 20 are longitudinally displaced from the upper ends of the container 2

and cover 4 respectively, such that when the locking member 12 is moved from its unlocked position (Figure 2) to its locked position (Figure 3), the locking projection 20 engages the outer wall of the container 2 immediately below its projection 6. In the locked position, the upper part 22 of the locking member 12 passes over the container 5 rim 8 with its free hooked end 24 snap-fitting over a locally-thickened wall portion 26 of the raised rim of the cover 4. This engagement of the locking member 12 onto the upper rim of the cover 4, whilst simultaneously bringing the projections 6 and 20 into engagement, is effected as a snap action, thus providing an audible indication that the cover 4 has been properly secured onto the container 2.

10

It will be appreciated, that, in the locked configuration, upward pressure on the free ends 24 of the locking members 12, will force the hinges 18 open so that the cover 4 removed from the container 2. Sealing and opening of the container 2 can be effected repeatedly.

15

It will also be noted, that the hinging of the locking members 12 on the cover skirt 14 is on the outside of the container 2, and thus is not, in normal use, contacted by the container contents. Thus there is no interference of the locking members 12 by the contents of the container 2.

Claims

1. Closure arrangement for a container, wherein the container has a peripheral wall defining a rim enclosing an opening at one end thereof, the peripheral wall having at least one outwardly-directed projection extending at least partially around the outer surface of the wall adjacent the opening, and wherein a cover is provided for releasably closing the opening, the cover having a surface for closing the opening of the container and a skirt depending therefrom to enclose the projection of the container, the skirt being provided with (a) at least one hinged locking member that has an inwardly-directed projection for co-operating with the outwardly-directed projection of the container, and (b) a lip for engaging over the rim of the container at the opening thereof, thereby to lock the cover to the container, with the respective inwardly-and outwardly-directed projections engaging with each other.
- 15 2. Closure arrangement according to claim 1, wherein the cover and the skirt are integrally formed with one another.
3. Closure arrangement according to claim 1 or claim 2, wherein the or each locking member is integrally formed with the skirt.
- 20 4. Closure arrangement according to any one of the preceding claims, wherein a window is formed in the skirt at the peripheral location of the or each locking member, whereby upon locking the cover onto the container, the locking member fits into its window and the respective inwardly- and outwardly-directed projections engage each other directly.
- 25 5. Closure arrangement according to any one of the preceding claims, wherein the lip of the skirt, upon locking the cover to the container, engages over a rim of the cover that is arranged to lie within the peripheral wall of the container adjacent the rim thereof.

6. Closure arrangement according to claim 5, wherein the thickness of the rim of the cover is locally increased in the region of the or each hinged locking member.

5 7. Closure arrangement according to any one of the preceding claims, wherein the or each hinged locking member is arranged to snap-fit over the rim of the container.

8. Closure arrangement according to any one of the preceding claims, comprising two or more, preferably three, of said hinged locking members.

10 9. Closure arrangement according to anyone of the preceding claims, of generally circular configuration.


10. Closure arrangement according to any one of the preceding claims, wherein the cover is made, preferably moulded, from a plastics material.

15 11. Closure arrangement for a container, substantially as hereinbefore described with reference to the accompanying drawings.

12. A container and a relockable closure arrangement therefor, the arrangement 20 being in accordance with any one of the preceding claims.

13. A container and closure arrangement according to claim 12, wherein the outwardly-directed projection of the container extends completely around the peripheral wall thereof.

25 14. A container and a relockable closure arrangement, substantially as hereinbefore described with reference to the accompanying drawings.






FIGURE 1.






FIGURE 2






FIGURE 3

PCT/GB2004/005103

